


VIVREAU Extra 50/85

Stylishly minimalistic.



ThermalGate™ • powerful thermal-disinfection feature supplied as standard and protects against retrograde contamination from external sources



Easy Access Panel additional control device (can be optionally installed and flexibly positioned)

The BRITA HygienePlus solution (which combines an inlet filter, thermal disinfection, and a bacterial filter) provides effective protection for dispensers. Developed on the basis of over 20 years' experience in the healthcare market, it is designed for environments where hygiene is of the utmost importance, and is optionally available for BRITA VIVREAU Extra 50/85.



- Medium or high capacity versions
- High-quality materials stainless steel
- Focus on sustainability R290 natural refrigerant and extremely low power consumption


- Ideal for e.g.**
- Executive lounges
 - Bars
 - Kitchenettes
 - Breakfast buffets
 - Staff rooms
 - Wellness and spa areas

Benefits

- Unlimited unchilled still or chilled still, sparkling or semi-sparkling water
- Only the tap is installed on the work surface; the cooler-carbonator is concealed below the counter
- Capacity: 50 l/h or 85 l/h


Two heights

- Tall tap (dispensing height: 330 mm)
- Short tap (dispensing height: 260 mm)



VIVREAU Extra 50/85

Technical data



Model	BRITA VIVREAU Extra 50	BRITA VIVREAU Extra 85	
Design / Type	Tap System		Easy Access Panel (optional)
Tap style	I-Shape		
Types of water			
Unchilled still	•	•	•
Chilled still	•	•	•
Semi-sparkling	•	•	•
Sparkling	•	•	•
Configuration options			
Hygiene feature: ThermalGate™		standard	
Hygiene feature: BRITA HygienePlus		optional	
Waste water container (installation without waste water connection)		optional	
Specifications			
Cooling capacity	50 l/h	85 l/h	
Unit dimensions: cooler-carbonator (W x H x D)	272 x 490 x 473 mm		
Unit dimensions	tall tap (H x D; Diameter): 453 x 165 mm; 70 mm short tap (H x D; Diameter): 385 x 165 mm; 70 mm		flat (W x H x D): 80 x 80 x 116 mm angled (W x H x D): 80 x 80 x 137 mm
Dispensing height	330 mm (tall tap) 260 mm (short tap)		
Weight	33 kg (cooler-carbonator) / 2.5 kg (tap)	38.5 kg (cooler-carbonator) / 2.5 kg (tap)	
Max. power consumption	440 W	540 W	
Max. flow rate	2 l/min		
Product number			
System with BRITA ThermalGate™	VIV E 50 I-33-C2-TG-I-CU (tall tap) VIV E 50 I-26-C2-TG-I-CU (short tap)	VIV E 85 I-33-C2-TG-I-CU (tall tap) VIV E 85 I-26-C2-TG-I-CU (short tap)	1040230 (Easy Access Panel)
System with BRITA HygienePlus	VIV E 50 I-33-C2-HP-I-CU (tall tap) VIV E 50 I-26-C2-HP-I-CU (short tap)	VIV E 85 I-33-C2-HP-I-CU (tall tap) VIV E 85 I-26-C2-HP-I-CU (short tap)	
Waste water container	1041216 VIV Waste Water Container-SP		

The food-grade quality and safety of BRITA water filter products are tested and verified by independent institutions



Product compliant with Reg. EC No 1935/2004

*applies to all materials that come into contact with water